

Date: 28.03.2025

POLYOLEFIN NON-ORIENTED CAST FILM – **VerCAST**

Technical Specification Sheet

1. **Product:** Non-oriented Polyolefin Film (CAST) – **VerCAST**.
2. **Product application:** used as a part of laminates or as individual packaging material.
3. **Direct food contact:** the film meets all local (Polish) and European Union requirements in the scope of materials and products intended to come into contact with food and foodstuff.
4. **Commercial denomination:** non-oriented polyolefin film, produced by Veroni-Pak is offered under the commercial denomination of **VerCAST**.
5. **Requirements:**
 - 5.1. **Side treatment:**
The surface of the film is usually treated on the external side of the reel.

It is also possible to treat the film on the inner side of the reel at the request of the buyer.
 - 5.2. **Unit:**
Non-oriented polyolefin film **VerCAST** is sold in reels. The film is wound on a cardboard sleeve with the inner diameter of 76 or 152 mm.
 - 5.3. **Defects:**
The following defects are to be foreclosed:
 - folds,
 - rucks,
 - oil stains,
 - telescopic effects,
 - damaged edges of a reel,
 - mechanical damages occurred while loading or shipping,
 - clamping of the sleeve,
 - cardboard sleeve being shorter than the reel itself,
 - sleeve falling out of the reel or being loose.
 - 5.4. **Allowable tolerance:**
 - thickness: +/- 6%,
 - width: ranging 200-2000mm +/- 2mm tolerance,
 - diameter reels ≤600mm,
 - permissible number of joints in the roll of film ≤2.

5.5. Marking of reels:

Each reel is marked with a self-adhesive label containing:

- production date,
- cutting date,
- product name,
- thickness of the film,
- width of the reel,
- length of the reel,
- external reel diameter,
- batch ID,
- order no.,
- no. of film joints in the reel,
- status of the control check,
- net weight of the film,
- treatment side of the film,
- pallet no.,
- batch no.,
- bar code.

6. Packing, storage and shipment:

VerCAST film is shipped on pallets, being the loading units, on which reels can be placed depending on the buyer's request:

- vertically,
- horizontally.

The manufacturer recommends film processing conditions: temperature 15 to 35°C and humidity 50% to 75% Rh. Compliance with these conditions ensures the specified properties of the films.

6.1. Markings of pallets:

Pallet units are marked with a label containing the following data:

- pallet no.,
- product name,
- client code,
- KKW no.,
- cutting date,
- net weight of the film,
- gross weight of the pallet,
- order no.,
- bar code,
- no. of reels on the pallet.

6.2. Storage:

Each pallet should be stored in roofed places in order to avoid the following:

- sunlight,
- different weather conditions,
- getting damp,
- getting wet.

Pallets should be stored at least 1.5 m from heat sources (heat generating devices). **Stacked pallets, covered with stretch film, should be unstacked as soon as possible, to allow proper air circulation.**

Storage or transportation of the **VerCAST** film under temperature below +15°C requires additional storage under further processing temperature for min. 24h.

Shipment:

VerCAST film should be shipped with roofed means of transport according to the current traffic regulations. Pallets should be secured against foreign odours, movement, getting dirty, damp and suffering any damage while being shipped.

7. Warranty:

The manufacturer guarantees the quality of VerCAST films [listed in these Technical Specification Sheet and Technical Data Sheets] on:

- the level of treatment of the films for a period of three months from the manufacturing date / stated on the winding label /,
- the other properties, specified in data sheets, of unprocessed VerCAST films for a period of six months from the manufacturing date.

To be sold as a full-fledged product released films are made no earlier than six months before the date of the sale, the properties of which have been positively verified by laboratory tests.

Treatment level is guaranteed for a period of three months from the date of production at a level ensuring the possibility of lamination and printing for min. 36 mN/m.

After 2 months from date of manufacture warranty dot. level of activation may be appropriately extended on the basis of laboratory tests performed. In this case, for specific information regarding the product batch. Warranty activation level is specified in the certificate of quality.

8. **Additional requirements** /under the Act on packaging and packaging waste; [Dz. U. 2020 poz. 1114]

Introducing company products in packaging must be submitted by the users of the product information on packaging and packaging waste in the area:

- a) the proper packaging waste management,
- b) the importance of markings on packaging,
- c) the impact of packaging waste on the environment and human health,
- d) available to return, collection and recovery, including recycling of packaging waste

This can be done by hanging the information at point of sale, issue leaflets and brochures, posters displaying or organizing competitions and events of information and education.